



US005483588A

United States Patent [19][11] **Patent Number:** **5,483,588****Eaton et al.**[45] **Date of Patent:** **Jan. 9, 1996****[54] VOICE PROCESSING INTERFACE FOR A
TELECONFERENCE SYSTEM**

[75] Inventors: Glenn A. Eaton, San Jose; Joseph A. McFadden, Palo Alto; Stuart A. Taylor, Menlo Park; Edward D. Tracy, Palo Alto; Emil C. W. Wang, Menlo Park, all of Calif.

[73] Assignee: Latitute Communications, Santa Clara, Calif.

[21] Appl. No.: 363,720

[22] Filed: Dec. 23, 1994

[51] Int. Cl.⁶ **H04M 3/56**

[52] U.S. Cl. **379/202; 379/67; 379/88;**
379/89; 379/62; 370/62; 370/110.1

[58] Field of Search **379/202, 201,**
379/207, 67, 88, 89; 370/62, 110.1; 348/14,
16

[56] References Cited**U.S. PATENT DOCUMENTS**

3,883,697	5/1975	Brown	370/62
4,059,735	11/1977	Betts	370/62
4,061,880	12/1977	Collins et al.	370/92
4,076,966	2/1978	Bovo et al.	370/62
4,153,817	5/1979	D'Ortenzio	370/62
4,225,956	9/1980	Betts et al.	370/62
4,229,814	10/1980	Betts	370/62
4,254,497	3/1981	Funderburk et al.	370/62
4,267,593	5/1981	Regan et al.	370/62
4,271,502	6/1981	Goutmann et al.	370/62
4,305,149	12/1981	Harrison	370/62
4,317,007	2/1982	Harrison	379/34
4,424,418	1/1984	Moore et al.	379/204
4,456,789	6/1984	Groves et al.	379/202
4,488,291	12/1984	Eschmann et al.	370/62
4,540,850	9/1985	Herr et al.	379/67
4,550,224	10/1985	Winchell	379/202
4,635,251	1/1987	Stanley et al.	370/62
4,796,293	1/1989	Blinken et al.	379/202
4,805,205	2/1989	Faye	379/96
4,809,262	2/1989	Klose et al.	370/62
4,922,490	5/1990	Blakley	370/110.1
4,937,856	6/1990	Natarajan	379/158
4,975,902	12/1990	Damany	370/62
5,012,509	4/1991	Nakamura et al.	379/53

5,020,098	5/1991	Celli	379/202
5,034,947	7/1991	Epps	379/202
5,128,989	7/1992	Nomura	379/158
5,136,581	8/1992	Muehrcke	379/202
5,163,084	11/1992	Kim et al.	379/88
5,195,086	3/1993	Baumgartner et al.	379/202
5,199,062	3/1993	Von Meister et al.	379/67
5,210,794	5/1993	Brunsgard	380/9
5,212,726	5/1993	Dayner	379/202
5,239,573	8/1993	Rangan	379/88
5,274,695	12/1993	Green	379/88
5,323,445	6/1994	Nakatsuka	379/202
5,369,694	11/1994	Bales et al.	379/206
5,373,549	12/1994	Bales et al.	379/93


Primary Examiner—Jeffery A. Hofsass

Assistant Examiner—Scott Wolinsky

Attorney, Agent, or Firm—Blakely, Sokoloff, Taylor & Zafman

[57] ABSTRACT

A teleconferencing system having screened introductions, named introductions, roll call, talker identification, and subconferencing, scheduling, and recording options. A caller attempting to join a teleconference is prompted to enter identification information by generating corresponding DTMF signals. The caller's identification is used to index the caller's profile stored in memory. The profile includes a memory address pointer to the location at which data representative of the spoken name of the caller is stored. The caller's identification is also checked against a list specified by the meeting organizer and stored in memory to determine whether the caller is to be admitted to the teleconference. If the caller is to be admitted to the teleconference, an announcement is generated to the attendees of the teleconference using the caller's spoken name retrieved from memory. Likewise, when the attendee leaves the conference, the system detects the attendee disconnecting and retrieves the attendee's spoken name stored in memory in order to generate an announcement to the attendees: "XYZ has left the conference." The system is responsive to requests by attendees during the teleconference. The attendees communicate with the system by depressing buttons on their touch tone phones which generate DTMF signals. The system also has the capability of scheduling new conferences and automatically checking for any conflicts.

60 Claims, 12 Drawing Sheets

US-PAT-NO: 5483588

DOCUMENT-IDENTIFIER: US 5483588 A
See image for Certificate of Correction

TITLE: Voice processing interface for a
teleconference system

----- KWIC -----

Detailed Description Text - DETX (17):

The voice file system 405, controlled by the user application module 404, stores and outputs voice data. More particularly, the voice file system 405 is coupled to the DSP array 410 and memory and enables real time support of a multi-port voice subsystem providing simultaneous playback and record operations as part of the automated teleconferencing services described herein. For example, when a caller wishes to join a teleconference, the spoken name of the caller is retrieved by the voice file system from the data storage subsystem and output to the DSP array 410. The DSP array 410 processes the name and outputs the signals subsequently through the switching matrix 402 to line cards 401 for communication of a verbal announcement to the conference participants that the caller, identified by the spoken name, is joining the conference.

Current US Original Classification - CCOR (1):
379/202.01

Current US Cross Reference Classification - CCXR (1):
370/260

Current US Cross Reference Classification - CCXR (2):
370/264

Current US Cross Reference Classification - CCXR (4):
379/204.01